



JK-798DIII

Automatic Overlock Machine
Automatic Suction by Pneumatic


Advantages:




Easy to Operate



Automatic Thread Trimming



Automatic Suction by Pneumatic



Auto-sensing Quick Start Sewing

				(mm)	(mm)	(mm)		(mm)	(S.p.m)	(mm)	NW/GW (kg)	
JK-798DIII-3-504-02/233	9#	1	3	-	4	3.8	0.7-2	5	7000	505x360x565	29.2/39.8	
JK-798DIII-3-504-32R2/223	9#	1	3	-	1.5	3.8	0.7-2	5	7000	505x360x565	29.2/39.8	
JK-798DIII-4-514-M03/333	9#	2	4	2	4	4.2	0.7-2	5.5	7000	505x360x565	29.2/39.8	
JK-798DIII-4-514-M03/333/H/M	11#	2	4	2	4	4.2	0.7-2	6	7000	505x360x565	29.2/39.8	
JK-798DIII-5-516-03/333	14#	2	5	3	4	3.8	0.7-2	5	7000	505x360x565	29.2/39.8	
JK-798DIII-5-516-03/233	14#	2	5	5	5	3.8	0.7-2	5	7000	505x360x565	29.2/39.8	
JK-798DIII-5-516-A04/435	19#	2	5	5	6	5	0.8-1.5	7	6500	505x360x565	29.2/39.8	
JK-798TDI-4-514-M03/333	9#	2	4	2	4	4.2	0.7-2	5.5	7000	472x360x495	29.5/37	
JK-798TDI-5-516-A04/435	19#	2	5	5	6	5	0.8-1.5	7	6500	472x360x495	29.5/37	
JK-798TDI-5-516-03/333	14#	2	5	3	4	3.8	0.7-2	5	7000	472x360x495	29.5/37	
JK-798TDI-4-514-A04/435	11#	2	4	2	4	6.5	0.8-1.5	6	6500	472x360x495	29.5/37	
JK-798TDI-5-516-03/233	14#	2	5	5	5	3.8	0.7-2	5	7000	472x360x495	29.5/37	

JK-798DIII by pneumatic; JK-798EP by electricity